

"How to Order" – VS & VSR Lubrication System

Continuous & Pulse Spray Applications

Product Type

- Valve Stack Without Reservoir VS
- Valve Stack With Reservoir VSR
- Injector Stack (No Controls)..... INJ

Control Type (Electrical/Pneumatic/Connector Timer)

- 120 VAC A
- 220-240 VAC, 50/60Hz B
- 24 VDC (European Version)*--see below C
- 24 VDCD
- Pneumatic Controls) P
- No Solenoid (INJ only)..... X

- Millennium Timer Options {connector timer} Operating Range**
- (1) MCT 120V; (2) MCT 240V; (3) MCT 24VDC (2.1 to 200 seconds)
 - (4) MPT 120V; (5) MPT 240V; (6) MPT 24VDC (0.5 to 5 seconds)
 - (7) MCT 120V; (8) MCT 240V; (9) MCT 24VDC (4 to 400 seconds)
- Substitute the number for the letters above for electrical options.

Regulator

- Single Regulator S
- Dual Regulator D
- Spit Option W
- No Regulator (INJ only) X

Injector Size

- Half-Drop Injector H
- Two Drop Injector T
- Combination of "H" & "T" injectors B

Number Of Injectors

- Range from "1" to "8".....

Regulator Options

- One Regulator X1
- Two Regulators - # of injectors/regulator (first digit/first regulator; second digit/second regulator)
- No Regulators (INJ Only)..... XX
- Split Option – Spray Nozzles/Drip Nozzles {must have "W" option in regulator field}
- Half & Two Drop Injectors - respectively (first digit/half drop injectors; second digit/two drop injectors – must have "B" in the injector field)

Fitting Location

- In-Line Location IL
- Low-Profile Location LP
- No Fittings XX

Type Of Fitting

- (Oil Lines: Nylon: 3/16" O.D. Tubing Steel Tube: 1/8" O.D. Tubing)
 (Air Lines: Nylon/Steel: 1/4" O.D. Tubing)
- Nylon Push In Fittings NY
 - Nylon Compression Fittings NC
 - Steel Tube Fittings: Carbon Steel CS
 - Steel Tube Fittings: Stainless Steel SS
 - No Fittings XX

Reservoir Fill Options {omit for VS or INJ product}

- Manual Fill M
- Central Fill P
- Manual Fill/High Level Switch MH
- Central Fill/High Level Switch PH

{low-level feedback is a standard in all reservoirs except pneumatically controlled version}

* DIN 43650 (LED & Surge Suppressor) solenoid connectors with metric tube fittings.

"IL" fitting location



"LP" fitting location



VS Series shown here